



Canon PowerShot S410 Motherboard Battery Replacement

Replacing a dead motherboard battery.

Written By: Ryan Bolton



INTRODUCTION

This guide shows you how to remove the motherboard battery and replace it with a new one.



TOOLS:


- [Phillips #0 Screwdriver](#) (1)
 - [iFixit Opening Tools](#) (1)
-

Step 1 — Battery




- ❗ Turn the camera with the bottom side facing up.
 - Locate the panel labeled "Batt. Open"
 - Place your finger on the panel and slide it in the direction of the arrow.
 - The slot will swing open revealing the battery pack.

Step 2



- ❗ Rotate the camera so that the slot is horizontal.
 - Pull the orange lever and the battery will spring out slightly.

Step 3




- Grasp battery and fully pull out of slot
- ⓘ When placing the new battery back in the slot, the arrow on the battery must align with the arrow on the camera.

Step 4 — Back Cover



- ⓘ Start by laying the camera flat with the LCD screen facing up.
- Remove the 3.8mm screw in the upper right corner.

Step 5



i Position the camera with the bottom facing up.

- Remove the 4.8mm screw.
- Remove the two 2.3mm screws.

Step 6



i Position the camera so that the rubber "AV Out Digital" tab is facing upward.

- Slide this rubber tab out of the way to reveal the bottom screw.
- Remove the two 3.7mm screws.


Step 7



- ① Turn the camera with the back side facing you.
- Grip the edges of the back plate, and carefully slide it off.
- ⚠ If there is any resistance in movement, double check there are no screws left in the chassis.

Step 8 — Front Cover



-  Orientate the camera as in the picture.
- Remove the two 2.3mm outer screws.
 - Remove the two 3.8mm screws near the strap bracket.
 - Remove small panel covering mounting bracket.
 - Remove door covering memory card.

Step 9



- ① Rotate the camera so that the bottom side is facing you.
- Remove the 3.8mm screw below the mounting bracket.

Step 10



- ① Rotate the camera so that the front is facing you.
- Grasp sides of front cover and carefully pull the front panel off of the camera.

Step 11 — Motherboard Battery



- ① Position the camera so that the motherboard is facing you.
- Remove the plastic flap covering the motherboard.
- Place edge of iPod Opening Tool in the small opening between the battery and the motherboard.
- Pry the battery off of the motherboard using the iPod Opening Tool.

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-07-08 02:17:10 AM.